



- 1 Provides OE with a robust design alternative to flat flange
- 2 Provides rotational and axial alignment flexibility

NORMACONNECT®

Robust alternative clamp

The NORMACONNECT® AccuLock exhaust clamp provides a robust alternative to flat flanges with enhanced assembly flexibility, lower weight and improved overall value. Designed for use in low leak, pre- and after-treatment (catalyst) applications. Uses less space than a flat flange joint and has positive axial retention.

Advantages at a glance

- Enhanced assembly flexibility, lower weight, improved overall value
- Positive axial retention
- Uses less space than a flat flange joint

Applications

Designed for use in low leak, pre- and after-treatment (catalyst) applications

Materials

- Aluminized steel
- 409 stainless steel
- 430 stainless steel

Information

Available in standard industry sizes from 55 mm (2 1/5") up to 387.6 mm (15 1/3")

Technical data & Ordering information

NORMACONNECT® ACCULOCK					
Designation	Diameters		Aluminized Steel Product No.	409 Stainless Steel Product No.	430 Stainless Steel Product No.
	in mm	in inches			
ACCULOCK 55	55	2 1/5"	0370 0000 055		
ACCULOCK 63.5	63.5	2 1/2"	0370 0001 064		
ACCULOCK 88.9	88.9	3 1/2"	0370 0002 089	0370 0000 089	
ACCULOCK 336.8	336.8	13 1/3"			0370 0001 337
ACCULOCK 362.2	362.2	14 1/3"			0370 0001 362
ACCULOCK 387.6	387.6	15 1/3"			0370 0001 388