



- 1 Hexagonal socket bolt with washer
- 2 Square nut
- 3 Closure unit
- 4 Collar
- 5 Sealing sleeve

The fast connection with quick release closure

The NORMACONNECT® DCS RAPID MSM connection is easy-fitting and thus especially suitable for repair purposes. It is the fast connection with quick release closure for non-pull-out resistant connections.



Materials


| | | | | |
|----|----|----|----|----|
| W1 | W2 | W3 | W4 | W5 |
| | x | | | |

- W2**
- Material, Collar: AISI 430 Ti
 - Material, Clamping unit: AISI 304 / AISI 430 Ti
 - Material, Bolts/Nuts: Steel, surface protected
 - Material, Sealing sleeve: EPDM

Information

- Resisting axial pull-out forces up to max. 0.5 bar
- Defined locking torque without using a special tool
- Meeting the fire protection requirements

Technical data & Ordering information



| NORMACONNECT® DCS RAPID MSM | | | | | | | | | |
|-----------------------------|----------------------------------|--------|--------|--------|-------------|---------------|-----------|----------------|--|
| Designation | Max. Dimensions after Assembly ~ | | | | | | | W2 Product No. | |
| | DN | D (mm) | H (mm) | L (mm) | P max (bar) | Torque (Nm) | Bolt (mm) | | |
| RAPID DN 50 MSM | 50 | 70 | 80 | 40 | 0.5 | Tight-Locking | M 8 | 0245 8257 050 | |
| RAPID DN 70 MSM | 70 | 90 | 100 | 40 | 0.5 | Tight-Locking | M 8 | 0245 8258 070 | |
| RAPID DN 80 MSM | 75/80 | 95 | 105 | 40 | 0.5 | Tight-Locking | M 8 | 0245 8260 080 | |
| RAPID DN 100 MSM | 100 | 125 | 135 | 46 | 0.5 | Tight-Locking | M 8 | 0245 8261 100 | |
| RAPID DN 125 MSM | 125 | 147 | 162 | 55 | 0.5 | Tight-Locking | M 8 | 0245 8262 125 | |
| RAPID DN 150 MSM | 150 | 172 | 187 | 55 | 0.5 | Tight-Locking | M 8 | 0245 8263 150 | |
| RAPID DN 200 MSM | 200 | 227 | 244 | 70 | 0.5 | Tight-Locking | M 10 | 0245 8264 200 | |