



- 1 High-strength fastener hardware with corrosive resistant coating
- 2 Improved clamp performance for thicker pipes on larger pipe gaps
- 3 Easy to assemble, only one assembly torque point
- 4 Reaction block serves as a defined stop, avoiding pipe deformation

Extra seal clamp

The NORMACONNECT® DuraSeal offers extra seal and clamp load performance to meet or exceed durability requirements without permanent distortion to exhaust members. Designed for applications with thicker pipe walls and larger pipe assembly gaps, it is ideal for applications with limited

packaging space.



Advantages at a glance

- Exclusive reaction block provides a full 360° distribution
- Simple, effective way to connect exhaust system components
- Designed for part-in-assembly pre-attachment
- Pre-assembled for easy installation
- Provides joint serviceability; no permanent distortion

Applications

- For high durability requirements
- Improved clamp performance for applications with thicker pipe walls and larger pipe assembly gaps
- Ideal for applications with limited packaging space
- Pipes, mufflers and converters

Materials

- 409 stainless steel
- 304 stainless steel (on request)

Information

- Diameter range: 50.8 mm (2") up to 127 mm (5")
- 7.9 mm (5/16") slotted hex screw

Technical data & Ordering information

NORMACONNECT® DURASEAL			
Designation	Diameters		409 Stainless Steel Product No.
	in mm	in inches	
DURASEAL 50.8	50.8	2"	0371 0001 056
DURASEAL 57.15	57.15	2 1/4"	0371 0001 062
DURASEAL 63.5	63.5	2 1/2"	0371 0003 068
DURASEAL 69.85	69.85	2 3/4"	0371 0003 075
DURASEAL 76.2	76.2	3"	0371 0004 081
DURASEAL 88.9	88.9	3 1/2"	0371 0000 093
DURASEAL 101.6	101.6	4"	0371 0001 107
DURASEAL 114.3	114.3	5"	0371 0000 132